

| | 1.4 8v 70 HP | 1.4 8v 78 HP | 0.9 TwinAir Turbo 105 HP | 1.4 TP 140 HP TCT | 1.4 TP 170 HP TCT | |
|--|--|-------------------------|--------------------------|---|--|--|
| TECHNICAL SPECIFICATIONS | | | | | | |
| SPECIFICATIONS | No. of cylinders, layout | 4 | 4 | 2 | 4 | |
| | Bore x stroke (mm) | 72x84 | 72x84 | 80.5x86 | 72x84 | |
| NORMAL | Displacement (cm³) | 1368 | 1368 | 875 | 1368 | |
| | Compression ratio | 11.1:1 | 11.1:1 | 10:01 | 9.8:1 | |
| | Maximum power output kW (HP - EC) at rpm (NATURAL) NOR | 51 (70) at 6000 rpm | 57.3 (78) at 6000 rpm | 72 natural (5750)/ 77 dynamic (5500) | 102 (140) at 5000 rpm | 125 (170) at 5500 rpm |
| | Peak torque Nm (kgm - EC) at rpm (NORMAL) | 115 (11.76) at 3000 rpm | 115 (11.76) at 3000 rpm | 120 (12.2) at 1750 rpm | 230 (23.4) at 2500 rpm | |
| | Peak torque Nm (kgm-EC) at rpm (DYNAMIC) | | | 145 (14.8) at 2000 rpm | 250 (25.5) at 2500 rpm | |
| | Fuel | Aspirated | Aspirated | ELECTRONIC INJECTION Timed sequential multipoint with knock control | Turbocharged by means of exhaust gas turbocharger with engine load management by means of variable intake valve activation | Turbocharged by means of exhaust gas turbocharger with engine load management by means of variable intake valve activation |
| | Stop&Start system for automatic engine stopping/starting for short stops during city driving, useful for optimising fuel consumption and CO ₂ emissions | ND | Standard | Standard | Standard | Standard |
| | TRANSMISSION | Drive | Front | Front | Front | Front |
| | | Transmission | Manual, 5-speed | Manual, 5-speed | Manual, 6-speed | Twin clutch |
| | TYRES | Standard trim level | 195/55 R16 | 195/55 R16 | 195/55 R16 | 215/45 R17 |
| SUSPENSION | Front | MacPherson | MacPherson | MacPherson | MacPherson | |
| | Rear | Torsion beam | Torsion beam | Torsion beam | Torsion beam | |
| BRAKES | Front (mm) | 257 | 257 | 257 | 305 | |
| | Rear (mm) | 251 | 251 | 251 | 251 | |
| DIMENSIONS | Wheelbase (mm) | 2511 | 2511 | 2511 | 2511 | |
| | Length / width (mm) | 4063/1720 | 4063/1720 | 4063/1720 | 4063/1720 | |
| | Height (mm) | 1446 | 1446 | 1446 | 1446 | |
| | Track (mm) | 1483/1475 | 1483/1475 | 1483/1475 | 1483/1475 | |
| | Luggage compartment capacity (dm³) | 270 | 270 | 270 | 270 | |
| | Overhang | 904 | 904 | 904 | 904 | |
| CAPACITIES - WEIGHTS | Fuel tank (litres) | 45 | 45 | 45 | 45 | |
| | Kerb weight (kg) | 1065 | 1070 | 1130 | 1170 | |
| PERFORMANCE | Max. towable weight (kg) braked | 500 | 500 | 500 | 500 | |
| | Max. speed (km/h) | 160 | 165 | 184 | 209 | |
| FUEL CONSUMPTION - EMISSIONS as per directive 1999/100/EC | Acceleration (1 person + 30 kg) 0-100 km/h (s) | 14 | 13 | 11.4 | 8.1 | |
| | Urban cycle consumption (l/100 km) | 7.6 | 7.3 | 5.0 | 7.0 | |
| | Extra-urban cycle (l/100 km) | 4.7 | 4.6 | 3.8 | 4.4 | |
| | Combined cycle (l/100 km) | 5.8 | 5.6 | 4.2 | 5.4 | |
| | CO ₂ emissions (g/km) | 134 | 130 | 99 | 124 | |
| | Environmental classification | Euro 6 | Euro 6 | Euro 6 | Euro 6 | |

| 1.3 JTDM 85 HP | 1.6 JTDM 120 HP | 1.4 TP 120 HP LPG |
|---|---|--|
| 4 | 4 | 4 |
| 69.6x82 | 79.5x80.5 | 72x84 |
| 1248 | 1598 | 1368 |
| 16.8:1 | 16.5:1 | 9.8:1 |
| 62(85) at 3500 rpm | 88 (120) at 3750 rpm | 88 (120) at 5000 rpm |
| 200 at 1500 rpm | 280 (28.6) a 1500 rpm 320 (32.6) at 1750 rpm | 206 (21) at 1750 rpm |
| Electronically controlled Common Rail Multijet direct injection with turbocharger and intercooler | Electronically controlled Common Rail Multijet direct injection with turbocharger and intercooler | Supercharged with exhaust gas turbocharger |
| Standard | Standard | ND |
| Front | Front | Front |
| Manual, 5-speed | Manual, 6-speed | Manual, 5-speed |
| 195/55 R16 | 195/55 R16 | 195/55 R16 |
| MacPherson | MacPherson | MacPherson |
| Torsion beam | Torsion beam | Torsion beam |
| 281 | 281 | 281 |
| 251 | 251 | 251 |
| 2511 | 2511 | 2511 |
| 4063/1720 | 4063/1720 | 4063/1720 |
| 1446 | 1446 | 1446 |
| 1483/1475 | 1483/1475 | 1483/1475 |
| 270 | 270 | 247 |
| 904 | 904 | 904 |
| 45 | 45 | 45 |
| 1150 | 1205 | 1145 (1197) |
| 1000 | 1000 | 500 |
| 174 | 198 | 198 |
| 12.9 | 9.9 | 8.8 |
| 4.4 | 5.2 | 10.6 / 8.2 |
| 2.9 | 3.7 | 6.6 / 5.1 |
| 3.5 | 4.3 | 8.1 / 6.2 |
| 90 | 112 | 131/145 |
| Euro 5+ | Euro 5+ | Euro 6 |